

SKIRT BOARD RUBBER SHEET

Abrasion & Impact Resistant | Fire & Chemical Resistant | Good Mechanical Strength



Overview

Duratuf Skirt Board Rubber Sheet is a blended natural and synthetic rubber strip designed for use as a sealing skirt along conveyor belts on conveyor systems. The Natural Skirting Rubber physical properties create a strong seal once adjusted. The Skirt Board Rubber Sheet is used to reduce material spillage and prevent dust pollution, while minimising wear to the conveyor belt.

The Skirt Board Rubber Sheet can be supplied as full slabs or as pre-cut skirting rubber strips to suit any standard conveyor system designs, ready for easy installation. It can also be supplied with pre-cut holes, slots and bevels, as per specifications and drawings or custom designed to meet any application requirements. They are offered in a variety of choices depending on its hardness, specific gravity, colour, fire resistance, mechanical properties & surface finish.



Technical Information

Product Code	Polymer	Sp. Gravity	Hardness (Shore A)	Tensile Strength (Min.)	Elongation (Min.)	Abrasion (Max.)	Colour	Temp. Range
SKB13065P (FR)	NR/CR (FR)	1.30	65° ± 5°	14 MPa	300%	250mm ³	Black	-25°C to +90°C
SKB12560P	NR	1.25	60° ± 5°	10 MPa	400%	125mm ³	Red	-20°C to +70°C
SKB12540P	NR	1.25	40° ± 5°	9 MPa	450%	125mm ³	Black	-20°C to +70°C
SKB14060S	NR	1.40	60° ± 5°	7 MPa	300%	200mm ³	Black	-20°C to +70°C
SKB15560C	NR	1.55	60° ± 5°	3.5 MPa	250%	350mm ³	Black	-20°C to +70°C
SKB CD	NR	1.20 to 1.60	40° ± 5° to 70° ± 5°	3 MPa to 21 MPa	200 to 750%	100mm ³ to 400 mm ³	Any	-30°C to +70°C

FR - Fire Resistant Grade | P - Premium Grade | S - Superior Grade | C - Commercial Grade | CD - Custom Design

Standard Thickness	3mm, 5mm, 6mm, 10mm, 12mm, 16mm, 20mm 25mm
Standard Roll Size	1200mm x 10Mtrs for upto 10mm & 1200mm x 5M for upto 25mm thick
Standard Strip Size	75mm, 100mm, 125mm, 150mm, 200mm, 250mm & 300mm wide x 20Mtr. Long
Standard Finish	Both Sides Smooth (SS)

Cut lengths, strips, custom shapes, surface finish and colours are available upon request

Note: Manufacturing tolerance of ± 10% on thickness, ± 5% on length & ± 2% on width shall be applicable

Applications

Duratuf Skirt Board Rubber Sheet has been designed primarily for use as a sealing side skirt along the conveyor belt on conveyor systems but can be used for any application which requires an economical rubber skirting strip.

Duratuf Soft 40 Duro Skirt Board Rubber Sheet is ideal for conveyor loading or transfer points but can be used in any application where a flexible and durable long-lasting seal is required. It is better in quality to standard skirting and offers a greater longevity in most applications.

Inquiry/Ordering Info

- > Thickness x Width x Length *
- > Hardness *
- > Specific Gravity *
- > Colour *
- > Surface Finish *
- > Fire Resistance
- > Tensile Strength & Elongation *
- > Total Quantity Required
- > Abrasion Resistance

* Mandatory